

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

1. (currently amended): An electro-hydraulic power steering apparatus comprising:
 - a first housing having a support portion;
 - a second housing fixed to the first housing;
 - a control device disposed in a space surrounded by ~~the one~~ a side of the first housing and ~~the one~~ a side of the second housing;
 - a motor disposed on ~~the other~~ another side of the first housing, the motor including a rotor, a stator and a frame, the rotor having a first bearing supported by the support portion and a second bearing, the stator having an iron core, the frame made of iron and making up an outer shell of the motor, the frame including an inner circumferential face into which the iron core is press fitted and a receiving portion which receives the second bearing;
 - a pump disposed on ~~the other~~ another side of the second housing;
 - a first clamp screw for securing the frame to the first housing; and
 - a second clamp screw for securing the first housing and the second housing;
- wherein the control device, the motor and the pump are integrated; and

the first clamp screw and the second clamp screw are tightened from the hand of the frame.

2. (original): The electro-hydraulic power steering apparatus according to claim 1, wherein the second housing has threaded portions; and

the first clamp screw includes a plurality of first clamp screws, in which part of the plurality of first clamp screws are tightened to the first housing, and the remainder are tightened to the threaded portions.

3. (original): The electro-hydraulic power steering apparatus according to claim 2, wherein the plurality of first clamp screws includes six first clamp screws disposed at substantially regular intervals;

two of the six first clamp screws are tightened to the first housing; and

the remaining four screws are tightened to the threaded portions.

4. (currently amended): The electro-hydraulic power steering apparatus according to claim 1,

wherein the second housing has a threaded portion to which the first clamp screw is screwed; and

the pump has a pump housing fixed by tightening a third clamp ~~screws~~ screw to the threaded portion from the hand of the pump.

5. (original): The electro-hydraulic power steering apparatus according to claim 1, wherein a sealant is coated on an abutment face between the first housing and the second housing and an abutment face between the first housing and the frame.

6. (original): The electro-hydraulic power steering apparatus according to claim 5, wherein at least one of the abutment face between the first housing and the second housing and the abutment face between the first housing and the frame has an outer circumference on which a step portion is provided.

7. (original): The electro-hydraulic power steering apparatus according to claim 6, wherein the step portion is provided with a chamfer.

8. (new): The electro-hydraulic power steering apparatus according to claim 1, wherein both the first clamp screw and the second clamp screw are accessible from outside of the first housing and the second housing.

9. (new): The electro-hydraulic power steering apparatus according to claim 4,
wherein the third clamp screw is accessible from outside of the second housing and is screwed
into the second housing in a direction towards the motor.

10. (new): The electro-hydraulic power steering apparatus according to claim 1,
wherein the pump is disposed distal to the motor.

11. (new): The electro-hydraulic power steering apparatus according to claim 1,
wherein the second clamp screw is disposed further from the motor than the first clamp screw.

12. (new): The electro-hydraulic power steering apparatus according to claim 1,
wherein the first clamp screw is screwed into the frame and the first housing in the same
axial direction that the second clamp screw is screwed into the first housing and the second
housing.